

JRP3 Input

IEC B5 Flange

SECTION A-A

Dimension	A	B	C	D	E	K	L	M	R	S
IEC 63	140	20	95G7	115	5	11H7	12,8	4Js9	45	M8
IEC 71	160	21	110G7	130	5	14H7	16,3	5Js9	45	M8
IEC 80	200	26	130G7	165	5	19H7	20,3	6Js9	45	M10
IEC 90	200	26	130G7	165	5	24H7	27,3	8Js9	45	M10
IEC 100	250	---	180G7	215	6	28H7	31,3	8Js9	45	M12
IEC 132	300	95	230G7	265	7	38H7	41,3	10Js9	45	M12

OMP flange

SECTION M-M

DETAIL N

Dimension	F	G	H
Shaft C	25	28	8
Shaft CB	32	35	10

Full shaft input

SECTION B-B

Dimension	a	B3	c	k	l	m
AD	165	118	60	40	43	12
ADM1	220	120	15	65	69	18
ADM2	272	144	39	65	69	18

JRP3 Body

1 stage 2 stage 3 stage 4 stage

Complete JRP3

Output flange size

JRP3 Output

Hollow shaft with shrinkdisk Full shaft with key

Hollow shaft with spline Full shaft with spline

Detail P2N03B

Detail P2N03D

QUANTITY:	DRAWING DESCRIPTION				
01	JRP3				
		© EURNORM DRIVE SYSTEMS B.V., THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH, UNLESS OTHERWISE EXPRESSLY AGREED TO IN WRITING BY EURNORM, REMAINS THE SOLE PROPERTY OF EURNORM, AND MAY NOT BE DISCLOSED, COPIED, REDISTRIBUTED, RETRANSMITTED, PUBLISHED OR USED TO CREATE DERIVATIVE WORKS.			
PROJECTION:	THIRD PROJECTION	DRAWN BY:	SCALE:	SIZE:	REVISION:
		Dmar	1:5	A3	
DATE DRAWN:	ORDER NUMBER:	DRAWING NUMBER:	SHEET:		
11-7-2019	-				